CUI Devices is now Same Sky! Learn More

same sky

Additional Resources: Product Page | 3D Model

SERIES: CFM-80BF | DESCRIPTION: DC AXIAL FAN

FEATURES

- dual ball bearing system
- 80 x 80 mm frame
- multiple speed options
- PWM/tachometer wires available

MODEL

	input voltage		input current[1]		input power[1]		rated speed[1]	airflow[2]	static pressure[3]	noise[4]
	rated (Vdc)	range (Vdc)	typ (A)	max (A)	typ (W)	max (W)	typ (RPM±10%)	(CFM)	(inch H_2O)	typ (dBA)
CFM-8015BF-120-213	12	10.8~13.2	0.06	0.09	0.72	1.08	2,000[5]	23.23	0.04	21.3
CFM-8015BF-130-301	12	10.8~13.2	0.17	0.26	2.04	3.12	3,000[5]	34.85	0.10	30.1
CFM-8015BF-140-363	12	10.8~13.2	0.30	0.45	3.60	5.40	4,000	46.47	0.18	36.3
CFM-8015BF-220-213	24	21.6~26.4	0.04	0.06	0.96	1.44	2,000[5]	23.23	0.04	21.3
CFM-8015BF-230-301	24	21.6~26.4	0.13	0.21	3.12	5.04	3,000[5]	34.85	0.10	30.1
CFM-8015BF-240-363	24	21.6~26.4	0.14	0.21	3.36	5.04	4,000	46.47	0.18	36.3
CFM-8020BF-125-273	12	10.8~13.2	0.06	0.08	0.60	0.96	2,500[5]	24.52	0.07	27.4
CFM-8020BF-135-346	12	10.8~13.2	0.10	0.15	1.20	1.80	3,500	34.33	0.14	34.7
CFM-8020BF-145-401	12	10.8~13.2	0.20	0.30	2.40	3.60	4,500	44.14	0.24	40.2
CFM-8020BF-155-444	12	10.8~13.2	0.30	0.45	3.60	5.40	5,500	53.94	0.35	44.5
CFM-8020BF-225-273	24	21.6~26.4	0.03	0.05	0.72	1.20	2,500[5]	24.52	0.07	27.4
CFM-8020BF-235-346	24	21.6~26.4	0.06	0.09	1.44	2.16	3,500	34.33	0.14	34.0
CFM-8020BF-245-401	24	21.6~26.4	0.12	0.18	2.88	4.32	4,500	44.14	0.24	40.2
CFM-8020BF-255-444	24	21.6~26.4	0.18	0.27	4.32	6.48	5,500	53.94	0.35	44.5
CFM-8038BF-1110-595	12	10.8~13.2	1.36	1.64	16.32	19.68	11,000	83.80	1.96	59.5
CFM-8038BF-1130-631	12	10.8~13.2	2.10	2.52	25.20	30.24	13,000	98.42	2.70	63.2
CFM-8038BF-1150-662	12	10.8~13.2	2.53	3.04	30.36	36.48	15,000	114.28	3.64	66.3
CFM-8038BF-2110-595	24	21.6~26.4	0.73	0.88	17.52	21.12	11,000	83.80	1.96	59.5
CFM-8038BF-2130-631	24	21.6~26.4	0.96	1.15	23.04	27.60	13,000	98.42	2.70	63.2
CFM-8038BF-2150-662	24	21.6~26.4	1.22	1.46	29.28	35.04	15,000	114.28	3.64	66.3

Notes:
1. At rated voltage, after 3 minutes.
2. At rated voltage, room temperature, 65% humidity, 0 inch H_2O static pressure.
3. At rated voltage, 0 CFM airflow.
4. Measured in an anechoic chamber as per ISO3745/GB4214-84 at rated voltage, with background noise 20±2 dBA at 1 m from the fan intake.
5. Typical rated speed is measured as RPM±350 at rated voltage.
6. All specifications are measured at 25°C, 65% relative humidity unless otherwise specified.

MODEL (CONTINUED)

	input voltage		input current[1]		input power[1]		rated speed[1]	airflow[2]	static pressure[3]	noise[4]
	rated (Vdc)	range (Vdc)	typ (A)	max (A)	typ (W)	max (W)	typ (RPM±10%)	(CFM)	(inch H_2O)	typ (dBA)
CFM-8038BF-445-401	48	43.2~52.8	0.10	0.15	4.80	7.20	4,500	37.35	0.50	40.1
CFM-8038BF-460-463	48	43.2~52.8	0.15	0.23	7.20	11.04	6,000	49.8	0.89	46.3
CFM-8038BF-475-512	48	43.2~52.8	0.18	0.27	8.64	12.96	7,500	57.46	1.20	51.2
CFM-8038BF-490-551	48	43.2~52.8	0.25	0.38	12.0	18.24	9,000	68.96	1.67	55.1
CFM-8038BF-4110-595	48	43.2~52.8	0.30	0.45	14.40	21.60	11,000	84.28	2.50	59.5
CFM-8038BF-4130-631	48	43.2~52.8	0.42	0.61	20.16	29.28	13,000	100.58	3.14	63.1
CFM-8038BF-4150-662	48	43.2~52.8	0.60	0.72	28.80	34.56	15,000	114.28	3.93	66.2

Notes:
1. At rated voltage, after 3 minutes.
2. At rated voltage, room temperature, 65% humidity, 0 inch H_2O static pressure.
3. At rated voltage, 0 CFM airflow.
4. Measured in an anechoic chamber as per ISO3745/GB4214-84 at rated voltage, with background noise 20±2 dBA at 1 m from the fan intake.
5. Typical rated speed is measured as RPM±350 at rated voltage.
6. All specifications are measured at 25°C, 65% relative humidity unless otherwise specified.

PART NUMBER KEY



INPUT

parameter	conditions/description	min	typ	max	units
operating input voltage	12 Vdc input models 24 Vdc input models 48 Vdc input models	10.8 21.6 43.2	12 24 48	13.2 26.4 52.8	Vdc Vdc Vdc
starting voltage	12 Vdc input models (CFM-8038BF-1110-595: 9.0 Vdc; CFM-8038BF-1130-631: 10.0 Vdc; CFM-8038BF-1150-662: 8.0 Vdc) 24 Vdc input models (CFM-8020BF-225-273 & CFM-8020BF-235-346: 12 Vdc) 48 Vdc input models (CFM-8038BF-4130-631: 35 Vdc)		7 14 30		Vdc Vdc Vdc

PERFORMANCE[7]

parameter	conditions/description	min	typ	max	units
rated speed	at rated voltage, 25°C, after 3 minutes	2,000		15,000	RPM
air flow	at 0 inch H_2O, see performance curves	23.23		114.28	CFM
static pressure	at 0 CFM, see performance curves	0.04		3.93	inch H_2O
noise	at 1 m, rated speed	21.3		66.3	dBA

Note: 7. See Model section on page 1 for specific values.

PROTECTIONS / FEATURES[8]

parameter	conditions/description	min	typ	max	units
auto restart	on all models				
polarity protection	on all models				
soft start	only available on CFM-8038BF models				
tachometer signal	available on “20” and “22” models				
PWM control signal	available on “22” models				

Notes: 8. See Application Notes for details.

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
insulation resistance	at 500 Vdc between frame and positive terminal	10			MΩ
dielectric strength	at 500 Vac, 60 Hz, 1 minute between housing and positive terminal			5	mA
safety approvals	UL/cUL 507, TUV (EN/IEC 62368-1:2020+A11)				
EMI/EMC	EN 55032:2015, EN 55035:2017				
life expectancy	at 40°C, 65% RH, 90% confidence level		70,000		hours
RoHS	yes				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature		-10		70	°C
storage temperature		-40		75	°C
operating humidity	non-condensing	35		85	%
storage humidity	non-condensing	35		85	%

PERFORMANCE CURVES

CFM-8015BF-120-213



CFM-8015BF-130-301



CFM-8015BF-140-363



CFM-8015BF-220-213



CFM-8015BF-230-301



CFM-8015BF-240-363



PERFORMANCE CURVES (CONTINUED)

CFM-8020BF-125-273



CFM-8020BF-135-346



CFM-8020BF-145-401



CFM-8020BF-155-444



CFM-8020BF-225-273



CFM-8020BF-235-346



PERFORMANCE CURVES (CONTINUED)

CFM-8020BF-245-401



CFM-8020BF-255-444



CFM-8038BF-1110-595



CFM-8038BF-1130-631



CFM-8038BF-1150-662



CFM-8038BF-2110-595



PERFORMANCE CURVES (CONTINUED)

CFM-8038BF-2130-631



CFM-8038BF-2150-662



CFM-8038BF-445-401



CFM-8038BF-460-463



CFM-8038BF-475-512



CFM-8038BF-490-551



PERFORMANCE CURVES (CONTINUED)

CFM-8038BF-4110-595



CFM-8038BF-4130-631



CFM-8038BF-4150-662



MECHANICAL

parameter	conditions/description	min	typ	max	units
motor	4 pole DC brushless				
bearing system	dual ball bearing				
direction of rotation	counter-clockwise viewed from front of fan blade				
dimensions	CFM-8015BF models: 80 x 80 x 15.4 CFM-8020BF models: 80 x 80 x 20.0 CFM-8038BF models: 80 x 80 x 38.0				mm mm mm
material	PBT (UL94V-0)				
weight	CFM-8015BF models: weight varies by model CFM-8020BF models: weight varies by model CFM-8038BF models: weight varies by model	50.8 55.1 222.0		55.1 61.0 254.0	g g g

MECHANICAL DRAWING

units: mm

2 wire versions (+Vin & -Vin): UL 1007, 26 AWG
3 wire versions (+Vin, -Vin, & tach): UL 1007, 26 AWG
4 wire versions (+Vin, -Vin, tach, & PWM): UL 1007, 26 AWG

MOUNTING SCREW (Pan Head)			
Screw Type	Size	Standard	Torque
Machine Screw	M4	JIS B1111-1974	7.5 kgf-cm
Self-tapping Screw	M5	JIS B1122 Type 2	7.5 kgf-cm

CFM-8015BF

WIRE CONNECTIONS	
Wire Color	Function
Red	+Vin
Black	-Vin
Yellow[9]	Tach Signal
Blue[9]	PWM



Notes: 9. Wires only present on versions with output signals.

MECHANICAL DRAWING (CONTINUED)

units: mm

2 wire versions (+Vin & -Vin): UL 1007, 24 AWG
3 wire versions (+Vin, -Vin, & tach): UL 1007, 24 AWG
4 wire versions (+Vin, -Vin, tach, & PWM): UL 1007, 28 AWG

MOUNTING SCREW (Pan Head)			
Screw Type	Size	Standard	Torque
Machine Screw	M4	JIS B1111-1974	4.5 kgf-cm
Self-tapping Screw	M4.8	JIS B1122 Type 2	5.5 kgf-cm

CFM-8020BF

WIRE CONNECTIONS	
Wire Color	Function
Red	+Vin
Black	-Vin
Yellow[9]	Tach Signal
Blue[9]	PWM



Notes: 9. Wires only present on versions with output signals.

MECHANICAL DRAWING (CONTINUED)

units: mm

2 wire versions (+Vin & -Vin): UL 1430, 24 AWG
3 wire versions (+Vin, -Vin, & tach): UL 1430, 24 AWG
4 wire versions (+Vin, -Vin, tach, & PWM): UL 1430, 24 AWG

MOUNTING SCREW (Pan Head)			
Screw Type	Size	Standard	Torque
Machine Screw	M4	JIS B1111-1974	4.5 kgf-cm
Self-tapping Screw	M4.8	JIS B1122 Type 2	5.5 kgf-cm

CFM-8038BF

WIRE CONNECTIONS	
Wire Color	Function
Red	+Vin
Black	-Vin
Yellow[9]	Tach Signal
Blue[9]	PWM



Notes: 9. Wires only present on versions with output signals.

APPLICATION NOTES

Locked Rotor Protection/Auto Restart

At rated voltage, the current will be reduced or shut down to protect the motor from damage in 72 hours of locked rotor condition. When the fan motor is locked by an external force, the device will temporarily turn off electrical power to the motor and restart automatically when the locked rotor condition is released.

Polarity Protection

Able to withstand 10 minutes of reverse polarity connection between the positive and negative wires without causing damage.

Tachometer Signal (Yellow Wire)

The tachometer signal is for detecting the rotational speed of the fan motor. The output will be a square wave when fan is operating and V_{FG} or V_{CE} depending on the locked rotor position when fan motor is locked (See Figures 1~2 below).

Figure 1: Tachometer Output Circuit



Output Type: Open Collector

Vs: (V_{FG})
5 V fan: 3.3~5 V
All others: 3.3~15 V
Ic≤5 mA
R≥Vs/Ic
V_{CE}(sat)≤0.5 V

Figure 2: Tachometer Output Waveform



4 Pole Motor

N=RPM
T=60/N (sec)
FG=1/T*2 (Hz)
N=FG*30

APPLICATION NOTES (CONTINUED)

PWM Signal (Blue Wire)

This wire is for speed control of the fan motor using a PWM input signal from the customer circuit (See Figure 3 below).

Figure 3: PWM Input Signal



PWM Duty Cycle (%) = T1/T x 100%

Model	PWM Frequency Range (kHz)	PWM VIH (V)	PWM VIL (V)
CFM-8015BF-120-213-22	0.3~45	2~6	0~0.6
CFM-8015BF-130-301-22	0.3~45	2~6	0~0.6
CFM-8015BF-140-363-22	0.3~45	2~6	0~0.6
CFM-8015BF-220-213-22	0.6~55	2.3~10	0~0.7
CFM-8015BF-230-301-22	0.6~55	2.3~10	0~0.7
CFM-8015BF-240-363-22	0.2~50	2.5~10	0~0.8
CFM-8020BF-125-273-22	0.3~80	2.5~5.5	0~0.6
CFM-8020BF-135-346-22	0.3~45	2~6	0~0.6
CFM-8020BF-145-401-22	1~50	2.8~5	0~0.6
CFM-8020BF-155-444-22	0.3~80	2.5~5.5	0~0.6
CFM-8020BF-225-273-22	0.6~55	2.3~10	0~0.7
CFM-8020BF-235-346-22	0.6~55	2.3~10	0~0.7
CFM-8020BF-245-401-22	0.6~55	2.3~10	0~0.7
CFM-8020BF-255-444-22	0.6~55	2.3~10	0~0.7
CFM-8038BF-1110-595-22	2~60	2.8~6	0~0.7
CFM-8038BF-1130-631-22	2~60	2.8~6	0~0.7
CFM-8038BF-1150-662-22	2~60	2.8~6	0~0.7
CFM-8038BF-2110-595-22	2~60	2.8~6	0~0.7
CFM-8038BF-2130-631-22	2~60	2.8~6	0~0.7
CFM-8038BF-2150-662-22	2~60	2.8~6	0~0.7
CFM-8038BF-445-401-22	0.8~60	2.8~5.5	0~0.6
CFM-8038BF-460-463-22	0.8~60	2.8~5.5	0~0.6
CFM-8038BF-475-512-22	0.8~60	2.8~5.5	0~0.6
CFM-8038BF-490-551-22	0.8~60	2.8~5.5	0~0.6
CFM-8038BF-4110-595-22	0.8~60	2.8~5.5	0~0.6
CFM-8038BF-4130-631-22	0.8~60	2.8~5.5	0~0.6
CFM-8038BF-4150-662-22	0.8~60	2.8~5.5	0~0.6

Soft Start

When the fan power is on, the current will increase slowly (~15 seconds) until the fan reaches the rated speed.

REVISION HISTORY

rev.	description	date
1.0	initial release	10/15/2021
1.01	added new models	01/21/2022
1.02	added PWM signal versions	05/19/2022
1.03	logo, datasheet style update	08/12/2022
1.04	updated PWM details	03/08/2024
1.05	CUI Devices rebranded to Same Sky	09/12/2024
1.06	added new models	01/15/2026
1.07	updated tolerance details on 80x15 mm models	05/08/2026

The revision history provided is for informational purposes only and is believed to be accurate.

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.