

Additional Resources: Product Page

date 11/05/2024

page 1 of 3

MODEL: CPG-20-SMT-B | DESCRIPTION: POGO PIN

FEATURES

- pogo pin
- surface mount
- gold plated



SPECIFICATIONS


parameter	conditions/description	min	typ	max	units
rated voltage				12	Vdc
rated current		-		2	А
contact resistance	at working height	-		30	mΩ
force	at minimum compression at working height at maximum compression	55 75 95	80 100 120	105 125 145	gf gf gf
mid stroke			0.7		mm
full stroke			0.9		mm
working height			2.6		mm
life		10,000			cycles
operating temperature		-40		85	°C
RoHS	yes				

MECHANICAL DRAWING

units: mm tolerance: X.X: ±0.15 mm X.XX: ±0.10 mm PCB: ±0.05 mm unless otherwise noted

3.30±0.15	Ø1.25 - Ø0.80	- 0.80 - 3 - 0.80 king height 80±25g		. D - - -
ø1.15±0.05 -				

DESCRIPTION	MATERIAL	PLATING/COLOR
barrel	brass	outside: 0.05-0.4 µm min gold over 1.25-2.5 µm min nickel indise: 0.05 µm min gold over 0.25 µm min nickel
plunger	brass	1.0 µm min gold over 1.25-2.5 µm min nickel
spring	stainless steel wire	



→ ø1.55±0.05 -

Recommended PCB Layout Top View

Additional Resources: Product Page

SAME SKY | MODEL: CPG-20-SMT-B | DESCRIPTION: POGO PIN

date 11/05/2024 | **page** 3 of 3

REVISION HISTORY

rev.	description	date
1.0	initial release	11/05/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.